

ELETTROVALVOLA AD AZIONE MISTA ◀

GUIDED DIAPHRAGM PILOT OPERATED
SOLENOID VALVE
ÉLECTROVANNE À CHUTE FORCÉE

▶ **2/2 VIE - 2/2 WAYS - 2/2 VOIES**

SERIE 20000 - 2/2 VIE NORMALMENTE CHIUSE (N.C.)

SERIES 20000 - 2/2 WAYS NORMALLY CLOSED (N.C.)

SÉRIE 20000 - 2/2 VOIES NORMALEMENT FERMÉES (N.F.)

ART. 20000

▶ **AZIONE MISTA - 2/2 VIE - N.C. - CON BOBINA**
DIMENSIONI, PRESTAZIONI E PREZZI

APPLICAZIONI PRINCIPALI: IMPIANTI TERMOIDRAULICI, LAVASTOVIGLIE, IDROPULITRICI, IMPIANTI DI SOLLEVAMENTO A VENTOSA CON FLUIDI COME ACQUA, OLI LEGGERI, GAS INERTI E FLUIDI IN GENERE A BASSA VISCOSITÀ (FINO A 2°E OVVERO FINO A 12 CST).

GUIDED DIAPHRAGM - 2/2 WAYS - N.C. - WITH COIL
SIZE, PERFORMANCE AND PRICE

MAIN APPLICATIONS: THERMO-HYDRAULIC PLANTS, DISH-WASHERS, HIGH-PRESSURE WATER JET MACHINES, SUCTION LIFTING PLANTS WITH FLUIDS SUCH AS WATER, LIGHT OILS, INERT GAS AND LOW-VISCOSITY FLUIDS IN GENERAL (UP TO 2°E OR UP TO 12 CST).

CHUTE FORCÉE - 2/2 VOIES - N.F. - AVEC BOBINE
DIMENSIONS, PERFORMANCES ET PRIX

APPLICATIONS PRINCIPALES: INSTALLATIONS THERMOHYDRAULIQUES, LAVE-VAISSELLES, NETTOYEURS À JET D'EAU HAUTE PRESSION, SYSTÈMES DE LEVAGE À VENTOUSE AVEC FLUIDES TELS QUE EAU, HUILES LÉGÈRES, GAZ INERTES ET, EN GÉNÉRAL, FLUIDES À BASSE VISCOSITÉ (JUSQU'À 2°E, SOIT JUSQU'À 12 CST).



TENUTA
CON GUARNIZIONE IN
NBR - EPDM - FKM

CODICE - CODE	RIF. - REF.		PRESS. (bar)		KV (M3/H)
	F.F. (ØR)	DN	MIN	MAX	
20000-02-13...-A	G3/8	11,5	0	5	2,1
20000-03-13...-A	G1/2	13,5	0	5	2,4
20000-04-20...-A	G3/4	18	0	3	5
20000-05-25...-A	G1	26	0	3	7

NOTE:
TEMPERATURE DI IMPIEGO

NBR
EPDM
FKM

DA -10°C A +90°C
DA -10°C A +140°C
DA -10°C A +140°C

NOTE:
OPERATING TEMPERATURES

NBR
EPDM
FKM

FROM -10°C TO +90°C
FROM -10°C TO +140°C
FROM -10°C TO +140°C

NOTES:

TEMPÉRATURES DE FONCTIONNEMENT

NBR
EPDM
FKM

DE -10°C À +90°C
DE -10°C À +140°C
DE -10°C À +140°C